



Inline blower 400 and 200 series

AR 403 722

Metal housing.
Air extraction.
HVI CFM: 440, High Speed.
Inside Installation.

HVI Performance Values (CFM & SONES)

Blower Inline

Exhaust Discharge: horizontal
Speed: High speed
Static Pressure (in H₂O): 0.2"
HVI Wats: 95
CFM/Watt: 4.70
HVI CFM: 440
Sones (Reportable): NA

Blower Inline

Exhaust Discharge: horizontal
Speed: Low Speed
Static Pressure (in H2O): 0.2"
HVI Wats: 24
CFM/Watt: 9.51
HVI CFM: 220
Sones (Reportable): NA

Highlights

- Powerful inline blower to combine with motorless appliances AL400, VL200, VL414.
- Efficient BLDC technology.
- Compact and space-saving installation in a 4" (10 cm) high toe-kick.

Output

3 performance output levels and intensive mode:
Sound power and sound pressure depending on built-in situation.
Power levels depend on the downdraft appliances.

Features

3 electronically controlled power levels and 1 intensive mode.
Fan technology with highly efficient, brushless DC motor (BLDC).
Steel housing, zinc-plated.
Pipe connection pieces on intake side: 1 x 6" DN150 round.
Pipe connection pieces on output side: 1x DN150 flat duct.
Retaining bracket for installation on the ceiling or side of enclosed cabinet.

Planning notes

Inline blower in combination with AL400, VL200, VL414.
Connection to the respective appliances via network cable.
Installation in the toe-kick with cut-out for the air ducting in the cabinet base.

Connection

Total rating 180 W.
Total amps : 2 A 120 V / 60 Hz.
Includes a 60" (1.5 m) electrical cable.
Hardwire required.
78" (2 m) network cable included to connect with VL or AL downdraft.

