



## Vario 400 series freezer column RF 471

**RF 471 705**  
Fully integrated.  
Width 30" (76.2 cm).

### Included accessories

- 1 ice cube scoop.
- 1 ice storage container, large.
- 1 Accessory for side-by-side installation (RA 460 000).
- 1 supply hose, 47" (1.2 m) with 1/4" male compression fitting (standard icemaker connector).

### Installation accessories

**RA 421 713**  
Stainless steel door panel **with handle**.  
For 30" (76.2 cm) wide appliances,  
panel thickness 3/4".

**RA 423 140**  
Side trims used to conceal the gap  
between the appliance and adjacent  
cabinet. White powder coated metal.

**RA 425 110**  
Stainless steel handle for freezer door.  
With 3 mounts, length 4 1/2" (1,131 mm).

**RA 428 713**  
Stainless steel door panel, **handleless**.  
For 30" (76.2 cm) wide appliances,  
panel thickness 3/4".

**RA 460 012**  
Additional side heating element 110 V.  
Required if appliances are installed  
with a distance greater than 5/8" and  
less than 6 3/16" next to each other and  
for all built-in situations in a very  
humid environment. Not required if  
appliances are installed more than  
6 3/16" apart from each other.

**RA 460 020**  
Connecting element for custom  
cabinet fronts when panels are split  
vertically to create one door front.

**RA 464 714**  
Ventilation grill stainless steel  
For 30" (76.2 cm) wide appliances, with  
integrated water filter.

### Optional accessories

**RA 448 220**  
Ice storage container, small.

**RA 450 022**  
Water filter cartridge.

**Part #11037377**  
Water filter bypass for home water  
filtration system.



### Highlights

- Stainless steel interior with solid anthracite aluminum elements.
- Warm white and glare-free LED light spots.
- Opening assist for door with two options:
  1. Push-to-open function for integration into handleless cabinet front.
  2. Pull-to-open function to facilitate opening the door using a handle.
- The drawers in the RC and RF models are positioned at the same height. With side-by-side installation, the glass shelves and door bins can be aligned on the same level.
- Material and aesthetics of interior as for RC model
  - Glass shelves
  - Solid anthracite aluminum door bins.
- Flat stainless steel inner door, full-length.
- Almost invisible rail system for shelves and door bins for flexible positioning.
- Integrated automatic ice maker with fixed water connection.
- TFT touch display.
- ENERGY STAR® certified.
- Sabbath mode certified by Star-K.
- Net volume 15.8 cu.ft.

### Operation

TFT touch display operation.  
Clear text display in 52 languages.

### Features

Dynamic cold air distribution with Multi-Flow Air System.  
Automatic defrosting with defrost water evaporation.  
Cushioned door closing system.  
When rest mode is active, the appliance can only be opened using a handle.  
Open-door and malfunction warning system.

Home network integration for digital services (Home Connect) wireless via WiFi. The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country.  
For further information please check: [home-connect.com](http://home-connect.com).

### Freezing

No-frost technology with fast freezing at -22 °F.  
Temperature adjustable from 3 °F to -11 °F.  
4-star freezer compartment.  
Freezing capacity 11.7 kg/24 h.  
Storage time after a malfunction (14) h.  
4 safety glass shelves, white glass, 3 of which are individually height adjustable.  
2 fully extendable drawers with transparent front.  
Brilliant LED light spots with warm white, glare-free light.  
Flat door rail system with fully flexible positioning of door bins.  
4 height-adjustable door bins.

### Ice maker

Integrated automatic ice maker in the freezer compartment, with fixed water connection.  
Particle filter for water inlet, integrated in ventilation grille area.  
Saturation indicator shown in TFT touch display.  
Ice maker can be switched off independently.  
Ice cube production approx. 2.9 lb (1.5 kg)/24 h.  
Removable ice storage container with approx. 6.6 lbs. (2.5 kg) capacity.

### Consumption data

Energy consumption 479 kWh/year.  
Noise level 42 dB(A) re 1 pW.


### Planning notes

Flat hinge.  
Door hinge left, reversible.  
Door opening angle of 115°, fixable at 90°.  
For an installation with a door opening angle of 90°, the drawers have a restricted access.  
In case of door opening angle of 90° the standard ice storage container cannot be removed.  
A small ice storage container (RA 448 220) is available to ensure access. This change must be done prior to fixing the door.  
Max. door panel weight 55 lbs. (25 kg).  
Ships with white ventilation grill.  
Stainless steel grill is an optional accessory. No toe kick provided.  
Shut-off valve for water connection must be planned next to the appliance and always be accessible.  
If the water pressure exceeds 116 psi, connect pressure relief valve between water tap and hose set.

### Please read additional planning notes on page 248-257.

### Rating

Total rating 1,300 W/24 h.  
Total Amps: 10 A.  
Connecting cable 118" (3.0 m), detachable.  
Cold water connection required.  
Electrical location 6" above ground in lower left corner of unit.  
Supply hose 47" (1.2 m) with 1/4" male compression fitting (standard icemaker connector).  
Water pressure 29 to 116 psi.



The door face dimensions are designed for a maximum gap of 1/8" (3 mm).  
See more details on page 252.